



HEX. BOLT M-8X1.25X60 LG.-IS:1364(PART 1)-1983-A-8.8
Zn PLATED & YELLOW PASSIVATED CONDITION



FOR RESERVOIR MOUNTING:- 2 NOS,
COLUMN CLAMP MOUNTING:- 1 NO.

DRG. TRACED FROM M/S RANE POWER STG. LTD.
DRG NO. 69 04 08 08

<SC> :SIGNIFICANT CHARACTERISTICS ▽:CRITICAL CHARACTERISTICS										
BREAK SHARP CORNERS MAY BE EITHER A CHAMFER OR A RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.					MAHINDRA & MAHINDRA LIMITED TRACTOR DIVISION KANDIVLI (EAST), MUMBAI 400 101, INDIA.					
UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989					E.R. / PROC.REQ.NO : 6510		PART NO. : 005553016R1			
DIMENSIONS										
DIMENSIONS			mm.			INCHES				
	ABOVE	-	300	1000	-		-			
	UPTO	300	1000	-	-	-				
	NO DECIMAL (X.)	±1.5	±2.0	±3.0	-	-				
	ONE DECIMAL (0.X)	±0.8	±1.2	±1.5	±0.080	-				
	TWO DECIMAL (0.XX)	±0.3	±0.5	-	±0.030	-				
THREE DECIMAL (0.XXX)	-	-	-	±0.010	-	MATERIAL : -----				
				HEAT TREATMENT : -----						
		SHORTER SIDE OF ANGLES				NAME		SIGN	DATE	FIRST USED TRCR. MODEL
ABOVE		-	10	50	100	CAD ENGG.		S.S.Karle	27/1/94	-----
UPTO		10	50	100	-	DESIGNER				SCALE 1:1
ANGULAR TOLERANCE		±1°	±30'	±20'	±10'	CHECKER			2/2/94	SHEET 1 OF 1
PART OF THIS DRAWING / DOCUMENT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN PERMISSION OF M & M LTD.						APPR.BY			7/2/94	UNIT QTY. : 3
COMPUTER GENERATED DRAWING						DO NOT CHANGE MANUALLY		ALL DIMENSIONS ARE IN mm.		CHECK DRG WITH LATEST CHANGE No
IF IN DOUBT, ASK		DO NOT SCALE		DRG SIZE : A4						

ER13C0002346	AA		REDRAWN WITH 3D REF.	PG	NVC	RAW	23/10/13
E.R.NO.	LET	LOC	REVISIONS	DSNR	CKR.	APPR.	DATE